

Category		Code
Standard		FP
Seawater		FS
Foam Concentrate		FC

Valve Size	
1½"	40 mm
2"	50 mm
2½"	65 mm
3"	80 mm
4"	100 mm
6"	150 mm
8"	200 mm
10"	250 mm
12"	300 mm

Group	Model
Classic Deluge	Electrically Controlled Deluge Valve with EasyLock Manual Reset ⁽¹⁾⁽²⁾⁽³⁾
	Electro-Pneumatically Controlled Deluge Valve with EasyLock Manual Reset ⁽¹⁾⁽²⁾⁽³⁾
	Pneumatically Controlled Deluge Valve with EasyLock Manual Reset ⁽¹⁾⁽²⁾⁽³⁾
	Hydraulically Controlled Deluge Valve with EasyLock Manual Reset ⁽¹⁾⁽²⁾
	Hydraulically Controlled, Anti-Columning Deluge Valve with EasyLock Manual Reset ⁽¹⁾⁽²⁾
Combination Pressure Control Deluge	Electric Pressure Control Deluge Valve with Manual Reset
	Electric Pressure Control, On-Off Deluge Valve ⁽²⁾
	Electro-Pneumatic Pressure Control, On-Off Deluge Valve
	Pneumatic Pressure Control, On-Off Deluge Valve ⁽²⁾
	Hydraulic Pressure Control, On-Off Deluge Valve ⁽²⁾
On-Off Deluge	Electrically Controlled, On-Off Deluge Valve ⁽²⁾
	Electrically Controlled, On-Off Deluge Valve with Electric Remote Reset Latch ⁽²⁾
	Electro-Pneumatically Controlled, On-Off Deluge Valve
	Pneumatically Controlled, On-Off Deluge Valve ⁽²⁾
	Hydraulically Controlled, On-Off Deluge Valve ⁽²⁾
Manually Operated	Hydraulic Hydrant Valve
	Locally Operated Monitor Valve
	Pressure Regulating Hydrant Valve
Remote Control	Solenoid Activated, Remote Controlled Monitor Valve
	Electro-Pneumatically Operated, Remote Controlled Monitor Valve
	Pneumatically Operated, Remote Controlled Monitor Valve
Pre-action & Dry Pipe	Hydraulically Operated, Remote Controlled Monitor Valve
	Single Interlock Pre-action, Electric Release System ⁽²⁾⁽⁶⁾
	Double Interlock Pre-action, Electric-Electric Release System ⁽²⁾⁽⁶⁾
	Double Interlock Pre-action, Electric-Pneumatic Release System ⁽²⁾⁽⁶⁾
	Dry Pipe Control Valve ⁽²⁾⁽⁶⁾

January 2021

BERMAD Fire Protection Ordering Guide

FP		2"		400E-2M	
Category	Code	Group	Model	Code ⁽⁸⁾	
Standard	FP	Classic Deluge	Electrically Controlled Deluge Valve with EasyLock Manual Reset ⁽¹⁾⁽²⁾⁽³⁾	400E-2M	
Seawater	FS		Electro-Pneumatically Controlled Deluge Valve with EasyLock Manual Reset ⁽¹⁾⁽²⁾⁽³⁾	400E-3M	
Foam Concentrate	FC		Pneumatically Controlled Deluge Valve with EasyLock Manual Reset ⁽¹⁾⁽²⁾⁽³⁾	400E-4M	
			Hydraulically Controlled Deluge Valve with EasyLock Manual Reset ⁽¹⁾⁽²⁾	400E-1M	
			Hydraulically Controlled, Anti-Columning Deluge Valve with EasyLock Manual Reset ⁽¹⁾⁽²⁾	400E-5M	
		Combination Pressure Control Deluge	Electric Pressure Control Deluge Valve with Manual Reset ⁽¹⁾⁽²⁾	400E-2MC	
			Electric Pressure Control, On-Off Deluge Valve ⁽²⁾	400E-3DC	
			Electro-Pneumatic Pressure Control, On-Off Deluge Valve ⁽²⁾	400E-6DC	
			Pneumatic Pressure Control, On-Off Deluge Valve ⁽²⁾	400E-4DC	
			Hydraulic Pressure Control, On-Off Deluge Valve ⁽²⁾	400E-5DC	
		On-Off Deluge	Electrically Controlled, On-Off Deluge Valve ⁽²⁾	400E-3D	
			Electrically Controlled, On-Off Deluge Valve with Electric Remote Reset Latch ⁽²⁾	400E-3D-RL	
			Electro-Pneumatically Controlled, On-Off Deluge Valve ⁽²⁾	400E-6D	
			Pneumatically Controlled, On-Off Deluge Valve ⁽²⁾	400E-4D	
		Manually Operated	Hydraulic Hydrant Valve	405-02	
			Locally Operated Monitor Valve	405-11	
			Pressure Regulating Hydrant Valve	420-HY	
		Remote Control	Solenoid Activated, Remote Controlled Monitor Valve	400E-3X	
			Electro-Pneumatically Operated, Remote Controlled Monitor Valve	400E-6X	
			Pneumatically Operated, Remote Controlled Monitor Valve	400E-4X	
		Pre-action & Dry Pipe	Hydraulically Operated, Remote Controlled Monitor Valve	400E-5X	
			Single Interlock Pre-action, Electric Release System ⁽²⁾⁽⁶⁾	400E-7M	
			Double Interlock Pre-action, Electric-Electric Release System ⁽²⁾⁽⁶⁾	400E-7BM	
			Double Interlock Pre-action, Electric-Pneumatic Release System ⁽²⁾⁽⁶⁾	400E-7DM	
		Pressure Control	Dry Pipe Control Valve ⁽²⁾⁽⁶⁾	400E-DP	
			Pressure Reducing Valve	420-00	
			Pressure Reducing Valve ⁽⁵⁾	720-UL	
			Pressure Relief Valve ⁽⁴⁾	430-UF	
			Pressure Relief Valve ⁽⁵⁾	730-UF	
			Pressure Relief Valve with Electric Override	430-59	
		Pressure Relief Valve with Electric Override	730-59		
		Level Control	Differential Pressure Sustaining Valve ⁽³⁾	436-00	
			Level Control Valve with Modulating Horizontal Float	450-60	
			Level Control Valve with Bi-Level Electric Float	450-65	
			Level Control Valve with Bi-Level Vertical Float	450-66	
			Level Control Valve with Altitude Pilot ⁽⁷⁾	450-80	

Category	Code
Standard	FP
Seawater	FS
Foam Concentrate	FC

Valve Size	
1½"	40 mm
2"	50 mm
2½"	65 mm
3"	80 mm
4"	100 mm
6"	150 mm
8"	200 mm
10"	250 mm
12"	300 mm

Notes:

- ⁽¹⁾ Deluge Valves With EasyLock Manual Reset are provided with Full Trim, including drain and indicating components (A items)
- ⁽²⁾ UL Listed for sizes 1½, 2, 2½, 3, 4, 6 & 8"
- ⁽³⁾ VdS Configuration for sizes 2, 3, 4, 6 & 8", Add "VDS" Suffix To Type Code (example: 400E-2M-VDS)
- ⁽⁴⁾ UL Listed and FM Approved for 2, 2½, 3, 4 & 6"
- ⁽⁵⁾ UL Listed for sizes 2, 2½, 3, 4, 6 & 8"
- Refer to the product catalog sheet for specific pressure rating
- ⁽⁶⁾ Pre-action & Dry Pipe Valves Including Full Trim (A) and Trimmed Check Valve
- ⁽⁷⁾ Altitude pilot adjustment Ranges :
 "M6" for 2-14 m / 7-46 ft (standard), "M5" for 5-22 m / 17-72 ft, "M4" for 15-35 m / 49-115 ft and "M8" for 25-70 m / 82-230 ft.
- ⁽⁸⁾ Replace the first code digit with "7" when 700 valve is selected

BERMAD Standard Configuration



G	C	A5	PR	4DC	NN	7P7K																																																																																																																								
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="background-color: #0056b3; color: white;">Valve Pattern</th> <th style="background-color: #0056b3; color: white;">Code</th> </tr> </thead> <tbody> <tr> <td style="background-color: #fce4d6;">Globe Type (400 Standard)</td> <td style="background-color: #fce4d6;">G</td> </tr> <tr> <td>Y Type (700 only)</td> <td>Y</td> </tr> <tr> <td>Angle (700 only)</td> <td>A</td> </tr> </tbody> </table> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="background-color: #0056b3; color: white;">Body Material</th> <th style="background-color: #0056b3; color: white;">Code</th> </tr> </thead> <tbody> <tr> <td style="background-color: #fce4d6;">Ductile Iron (Standard)</td> <td style="background-color: #fce4d6;">C</td> </tr> <tr> <td>Cast Steel</td> <td>S</td> </tr> <tr> <td>Stainless Steel 316</td> <td>N</td> </tr> <tr> <td>Bronze</td> <td>B</td> </tr> <tr> <td>Nickel Al. Bronze</td> <td>U</td> </tr> </tbody> </table> <p>For others consult BERMAD.</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="background-color: #0056b3; color: white;">End Connections</th> <th style="background-color: #0056b3; color: white;">Code</th> </tr> </thead> <tbody> <tr> <td style="background-color: #fce4d6;">ANSI #150RF (Standard)</td> <td style="background-color: #fce4d6;">A5</td> </tr> <tr> <td>ANSI#150FF</td> <td>a5</td> </tr> <tr> <td>ANSI#300RF ⁽¹⁾</td> <td>A3</td> </tr> <tr> <td>ISO-PN16</td> <td>16</td> </tr> <tr> <td>ISO-PN25 ⁽¹⁾</td> <td>25</td> </tr> <tr> <td>Grooved ANSI C-606-81⁽²⁾</td> <td>VI</td> </tr> </tbody> </table> <p>Notes: (1) 700 Models only (2) For 2", 3", 4", 6" and 8" only For others consult BERMAD.</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="background-color: #0056b3; color: white;">Coating</th> <th style="background-color: #0056b3; color: white;">Code</th> </tr> </thead> <tbody> <tr> <td style="background-color: #fce4d6;">Polyester Red (Standard)</td> <td style="background-color: #fce4d6;">PR</td> </tr> <tr> <td>High Built Epoxy Red</td> <td>ER</td> </tr> <tr> <td>Uncoated</td> <td>UC</td> </tr> </tbody> </table>	Valve Pattern	Code	Globe Type (400 Standard)	G	Y Type (700 only)	Y	Angle (700 only)	A	Body Material	Code	Ductile Iron (Standard)	C	Cast Steel	S	Stainless Steel 316	N	Bronze	B	Nickel Al. Bronze	U	End Connections	Code	ANSI #150RF (Standard)	A5	ANSI#150FF	a5	ANSI#300RF ⁽¹⁾	A3	ISO-PN16	16	ISO-PN25 ⁽¹⁾	25	Grooved ANSI C-606-81 ⁽²⁾	VI	Coating	Code	Polyester Red (Standard)	PR	High Built Epoxy Red	ER	Uncoated	UC	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="background-color: #0056b3; color: white;">Voltage - Main Valve Position (When Solenoid De-Energized)</th> <th style="background-color: #0056b3; color: white;">Code</th> </tr> </thead> <tbody> <tr> <td style="background-color: #fce4d6;">24VDC - N.C. (Standard)</td> <td style="background-color: #fce4d6;">4DC</td> </tr> <tr> <td>24VDC - N.O.</td> <td>4DO</td> </tr> <tr> <td>24VDC - Magna Latch</td> <td>4DS</td> </tr> <tr> <td>110VDC - N.C.</td> <td>5DC</td> </tr> <tr> <td>110VDC - N.O.</td> <td>5DO</td> </tr> <tr> <td>110V/50-60 - N.C.</td> <td>5AC</td> </tr> <tr> <td>110V/50-60 - N.O.</td> <td>5AO</td> </tr> <tr> <td>220V/50-60 - N.C.</td> <td>2AC</td> </tr> <tr> <td>220V/50-60 - N.O.</td> <td>2AO</td> </tr> </tbody> </table> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="background-color: #0056b3; color: white;">Tubing & Fittings</th> <th style="background-color: #0056b3; color: white;">Code</th> </tr> </thead> <tbody> <tr> <td style="background-color: #fce4d6;">Stainless Steel 316 (Standard)</td> <td style="background-color: #fce4d6;">NN</td> </tr> <tr> <td>Monel</td> <td>MM</td> </tr> </tbody> </table> <p>For others consult BERMAD.</p>	Voltage - Main Valve Position (When Solenoid De-Energized)	Code	24VDC - N.C. (Standard)	4DC	24VDC - N.O.	4DO	24VDC - Magna Latch	4DS	110VDC - N.C.	5DC	110VDC - N.O.	5DO	110V/50-60 - N.C.	5AC	110V/50-60 - N.O.	5AO	220V/50-60 - N.C.	2AC	220V/50-60 - N.O.	2AO	Tubing & Fittings	Code	Stainless Steel 316 (Standard)	NN	Monel	MM	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="background-color: #0056b3; color: white;">Options</th> <th style="background-color: #0056b3; color: white;">Code</th> </tr> </thead> <tbody> <tr> <td>Pressure Switch, General Purpose ⁽⁸⁾</td> <td>P</td> </tr> <tr> <td>Ex Proof Pressure Switch ⁽⁸⁾</td> <td>P7</td> </tr> <tr> <td>EExd ATEX Pressure Switch ⁽⁸⁾</td> <td>P9</td> </tr> <tr> <td>Single Limit Switch, General Purpose</td> <td>S</td> </tr> <tr> <td>Single Ex Proof, Limit Switch</td> <td>S7</td> </tr> <tr> <td>Single EExd Proximity Limit Switch</td> <td>S9</td> </tr> <tr> <td>Double EExd Proximity Limit Switch</td> <td>SS9</td> </tr> <tr> <td>Pressure Gauge Assembly ⁽⁸⁾</td> <td>6</td> </tr> <tr> <td>S.S Glycerin Pressure Gauge Assembly ⁽⁸⁾</td> <td>6n</td> </tr> <tr> <td>Monel Pressure Gauge Assembly ⁽⁸⁾</td> <td>6m</td> </tr> <tr> <td>Ex Proof NEC Class 1 Div.1 Solenoid</td> <td>7</td> </tr> <tr> <td>EExd ATEX Solenoid</td> <td>9</td> </tr> <tr> <td>Drip Check ⁽⁹⁾</td> <td>DC</td> </tr> <tr> <td>Drain Valve ⁽⁹⁾</td> <td>DV</td> </tr> <tr> <td>Manual Emergency Release Box ⁽⁹⁾</td> <td>D</td> </tr> <tr> <td>Mechanical Latching Pilot</td> <td>H</td> </tr> <tr> <td>Mechanical Latching Solenoid</td> <td>H1</td> </tr> <tr> <td>Magna-Latch Solenoid - 2 wires</td> <td>H2</td> </tr> <tr> <td>Magna-Latch Solenoid - 3 wires</td> <td>H3</td> </tr> <tr> <td>Water Motor Alarm Assembly ⁽⁸⁾</td> <td>W</td> </tr> <tr> <td>Special Elastomer ⁽¹⁰⁾</td> <td>E</td> </tr> <tr> <td>Large Control Filter</td> <td>F</td> </tr> <tr> <td>Valve Position Indicator</td> <td>I</td> </tr> <tr> <td>Junction Box</td> <td>J</td> </tr> <tr> <td>S.S. Solenoid Valve</td> <td>K</td> </tr> <tr> <td>S.S. 316 Trim Accessories ⁽¹¹⁾</td> <td>N</td> </tr> <tr> <td>Pressure Transmitter ⁽⁸⁾</td> <td>Q</td> </tr> </tbody> </table> <p>Notes: (8) Instrument Supplied loose. (9) Available for Models 3D, 4D, 5D, 6D, 3DC, 4DC, 5DC & 6DC only. (10) NBR or EPDM - Consult BERMAD for availability. (11) Not including Solenoid Valves & Pressure Gauges</p>	Options	Code	Pressure Switch, General Purpose ⁽⁸⁾	P	Ex Proof Pressure Switch ⁽⁸⁾	P7	EExd ATEX Pressure Switch ⁽⁸⁾	P9	Single Limit Switch, General Purpose	S	Single Ex Proof, Limit Switch	S7	Single EExd Proximity Limit Switch	S9	Double EExd Proximity Limit Switch	SS9	Pressure Gauge Assembly ⁽⁸⁾	6	S.S Glycerin Pressure Gauge Assembly ⁽⁸⁾	6n	Monel Pressure Gauge Assembly ⁽⁸⁾	6m	Ex Proof NEC Class 1 Div.1 Solenoid	7	EExd ATEX Solenoid	9	Drip Check ⁽⁹⁾	DC	Drain Valve ⁽⁹⁾	DV	Manual Emergency Release Box ⁽⁹⁾	D	Mechanical Latching Pilot	H	Mechanical Latching Solenoid	H1	Magna-Latch Solenoid - 2 wires	H2	Magna-Latch Solenoid - 3 wires	H3	Water Motor Alarm Assembly ⁽⁸⁾	W	Special Elastomer ⁽¹⁰⁾	E	Large Control Filter	F	Valve Position Indicator	I	Junction Box	J	S.S. Solenoid Valve	K	S.S. 316 Trim Accessories ⁽¹¹⁾	N	Pressure Transmitter ⁽⁸⁾	Q
Valve Pattern	Code																																																																																																																													
Globe Type (400 Standard)	G																																																																																																																													
Y Type (700 only)	Y																																																																																																																													
Angle (700 only)	A																																																																																																																													
Body Material	Code																																																																																																																													
Ductile Iron (Standard)	C																																																																																																																													
Cast Steel	S																																																																																																																													
Stainless Steel 316	N																																																																																																																													
Bronze	B																																																																																																																													
Nickel Al. Bronze	U																																																																																																																													
End Connections	Code																																																																																																																													
ANSI #150RF (Standard)	A5																																																																																																																													
ANSI#150FF	a5																																																																																																																													
ANSI#300RF ⁽¹⁾	A3																																																																																																																													
ISO-PN16	16																																																																																																																													
ISO-PN25 ⁽¹⁾	25																																																																																																																													
Grooved ANSI C-606-81 ⁽²⁾	VI																																																																																																																													
Coating	Code																																																																																																																													
Polyester Red (Standard)	PR																																																																																																																													
High Built Epoxy Red	ER																																																																																																																													
Uncoated	UC																																																																																																																													
Voltage - Main Valve Position (When Solenoid De-Energized)	Code																																																																																																																													
24VDC - N.C. (Standard)	4DC																																																																																																																													
24VDC - N.O.	4DO																																																																																																																													
24VDC - Magna Latch	4DS																																																																																																																													
110VDC - N.C.	5DC																																																																																																																													
110VDC - N.O.	5DO																																																																																																																													
110V/50-60 - N.C.	5AC																																																																																																																													
110V/50-60 - N.O.	5AO																																																																																																																													
220V/50-60 - N.C.	2AC																																																																																																																													
220V/50-60 - N.O.	2AO																																																																																																																													
Tubing & Fittings	Code																																																																																																																													
Stainless Steel 316 (Standard)	NN																																																																																																																													
Monel	MM																																																																																																																													
Options	Code																																																																																																																													
Pressure Switch, General Purpose ⁽⁸⁾	P																																																																																																																													
Ex Proof Pressure Switch ⁽⁸⁾	P7																																																																																																																													
EExd ATEX Pressure Switch ⁽⁸⁾	P9																																																																																																																													
Single Limit Switch, General Purpose	S																																																																																																																													
Single Ex Proof, Limit Switch	S7																																																																																																																													
Single EExd Proximity Limit Switch	S9																																																																																																																													
Double EExd Proximity Limit Switch	SS9																																																																																																																													
Pressure Gauge Assembly ⁽⁸⁾	6																																																																																																																													
S.S Glycerin Pressure Gauge Assembly ⁽⁸⁾	6n																																																																																																																													
Monel Pressure Gauge Assembly ⁽⁸⁾	6m																																																																																																																													
Ex Proof NEC Class 1 Div.1 Solenoid	7																																																																																																																													
EExd ATEX Solenoid	9																																																																																																																													
Drip Check ⁽⁹⁾	DC																																																																																																																													
Drain Valve ⁽⁹⁾	DV																																																																																																																													
Manual Emergency Release Box ⁽⁹⁾	D																																																																																																																													
Mechanical Latching Pilot	H																																																																																																																													
Mechanical Latching Solenoid	H1																																																																																																																													
Magna-Latch Solenoid - 2 wires	H2																																																																																																																													
Magna-Latch Solenoid - 3 wires	H3																																																																																																																													
Water Motor Alarm Assembly ⁽⁸⁾	W																																																																																																																													
Special Elastomer ⁽¹⁰⁾	E																																																																																																																													
Large Control Filter	F																																																																																																																													
Valve Position Indicator	I																																																																																																																													
Junction Box	J																																																																																																																													
S.S. Solenoid Valve	K																																																																																																																													
S.S. 316 Trim Accessories ⁽¹¹⁾	N																																																																																																																													
Pressure Transmitter ⁽⁸⁾	Q																																																																																																																													

Separate Items & System Components

Description	BERMAD Catalog Number
Water Motor Alarm Assy. (W) w/Strainer for Deluge/Preaction System	9901240028
AMD-74, Air Maintenance Device w/Regulator for External Pressure Supply	TEX0000003
AMD-75, Air Maintenance Device w/Regulator for External Pressure Supply - All S.S 316	Consult Bermad
AMD-76 Air Maintenance Device Regulated By-Pass Pressure Supply	TEX0000009
Standard Manual Release Station Model-D w/S.S. 304 Box-Brass valve	2920400093
S.S. 316 Manual Release Station Model-DN w/S.S. 316 Box	2920451093

BERMAD Standard Configuration





www.bermad.com

The information contained herein may be changed by BERMAD without notice. BERMAD shall not be held liable for any errors.
© Copyright 2010-2020 BERMAD CS Ltd. POXPE16 | November 2020