



Flow Control and Pressure Reducing Valve


IR-172-bDZ

The BERMAD Flow Control and Pressure Reducing Valve is a hydraulically operated, diaphragm actuated control valve that limits system demand and reduces downstream pressure to constant preset maximum values.



Features and Benefits

- Line Pressure Driven Hydraulic Flow Control
 - Limits fill-up rate and consumer over-demand
 - Protects downstream system
- Adjustable Servo Flow Pilot and 2-Way Pressure Reducing Pilot Controlled
 - Very low hysteresis
 - Easy flow and pressure setting
- Engineered Plastic Valve with Industrial Grade Design
 - Highly durable, chemical and cavitation resistant
- hYflow 'Y' Valve Body with "Look Through" Design
 - Ultra-high flow capacity - Low pressure loss
- Unitized Flexible Super Travel (FST) Diaphragm and Guided Plug
 - Accurate and stable regulation with smooth closing
 - Requires low actuation pressure
 - Prevents diaphragm erosion and distortion
- Internal "Differential Pressure Duct" Flow Sensor
 - No moving parts
 - Saves space and simplifies installation




Typical Applications

- Line Fill-Up Control
- Pressure Reducing Systems
- Multiple Independent Consumer Systems
- Systems Subject to Varying Supply Pressure

- [1] BERMAD Model IR-172-bDZ protects supply system from excessive flow, limits fill-up rate and consumer over-demand, and establishes reduced higher pressure zone.
- [2] BERMAD Solenoid Controlled Valve Model 210-N1
- [3] BERMAD Pressure Reducer Model 1½"-PRV
- [4] BERMAD Vacuum Breaker Model ½"-ARV

BERMAD Irrigation



IR-172-bDZ

For full technical details, refer to Engineering Section.

100 Series hYflow


Flow Control & Pressure Reducing

Technical Specifications

Dimensions and Weights

Pattern Size	DN Inch	Angle		Y (Oblique)			
		80-T 3-T	50-T 2-T	65-T* 2 1/2-T*	80-T 3-T	80L-T 3L-T	
L (L1)	mm	187 (130)	230	230	298	300	
	inch	7.4 (5.1)	9.1	9.1	11.7	11.8	
H (Hf)	mm	235 (245)	170 (185)	170 (185)	180 (195)	240	
	inch	9.3 (9.6)	6.7 (7.3)	6.7 (7.3)	7.1 (7.7)	9.5	
C	mm	53	140	140	140	180	
	inch	2.1	6	6	6	8	
h	mm	117	40	40	50	60	
	inch	4.6	1.6	1.6	2.0	2.4	
A; B	mm	320	135	135	190	190	
	inch	12.6	6	6	8	8	
Weight	Kg	1.6	1.35	1.4	1.6	3.0	
	lb.	3.5	3.0	3.1	3.5	6.6	

* 2 1/2"; DN65 Male Thread BSP-F, for PVC glue Unions.



Technical Data

Valve Configurations & Size:

Oblique: 2, 2 1/2, 3, 3L, 4 & 6"; DN50, 65, 80, 80L, 100 & 150

Angle: 3"; DN80

End Connections:

Threaded: 2, 2 1/2, 3 & 3"L; DN50, 65, 80 & 80L

Flanged: 3, 3L, 4, & 6"; DN80, 80L, 100 & 150

Grooved: 6"; DN150

Pressure Rating: 10 bar; 145 psi

Operating Pressure Range: 0.35-10 bar; 5-145 psi

Setting Range: 1-7 bar; 15-100 psi

Setting ranges vary according to specific pilot spring. Please consult factory.

Flow Setting Range: ±20% from valve predetermined flow

The "Differential Pressure Duct" is pre-determined in accordance with the desired flow.

Materials:

Body, Cover and Plug: Glass-Filled Nylon

Diaphragm: NR, Nylon Fabric Reinforced

Seals: NR

Spring: Stainless Steel

Cover Bolts: Stainless Steel

Control Accessories: Plastic


Tubing and Fittings: Plastic

How to Order


Please specify the requested valve in the following sequence: (for more options, refer to Ordering Guide.)

Sector	Size	Primary Feature	Additional Feature	Pattern	Construction Materials	End Connections	Control Type	Voltage - Main Valve Position	Additional Attributes
IR	2-4"	172	00	Y	P	FF	2W/3W	-	bDZ
	Other sizes available on request.								
		Oblique Angle (3"; DN80 Only)	Y A		Threaded BSP (Female) Threaded NPT (Female) Plastic Flanges* Metal Flanges* ("Corona")	BP NP FF CC	Servo Differential Pressure Duct Manual Selector Flow Stem Flow Stem with Position Indicator Low Preset Pressure (below 2 bar) Plastic Pressure Test Point		b D Z M MP 2 5
					* Comply to: ISO PN10, ANSI #125/150, Jis K-10, BS-D				Other attributes available on request

Flow Chart



Operation



The Shuttle Valve [1] hydraulically connects the Flow Pilot (FP) [2] or the Pressure Reducing Pilot (PRP) [3] to the Valve Control Chamber [4]. Pressure Differential ΔP across the Differential Pressure Duct [5] is in direct proportion to demand. The FP, continuously sensing ΔP , commands the Valve to throttle closed should demand rise above setting. The PRP commands the Valve to reduce Downstream Pressure [P2] to pilot setting. The Manual Selector [6] enables local manual closing.



info@bermad.com • www.bermad.com

The information herein is subject to change without notice. BERMAD shall not be held liable for any errors. All rights reserved. © Copyright by BERMAD. PC1AE72-Kb 05