

BURST CONTROL & PRESSURE REDUCING VALVE

Excessive Flow

Model 792-U EN/ES

Hydraulically operated, diaphragm actuated burst control & pressure reducing control valve with two independent functions: When flow is below setting, it reduces higher upstream pressure to lower pre-set downstream pressure, regardless of varying demand or upstream pressure. Upon sensing flow in excess of setting, it shuts off drip tight and locks until manually reset.

BERMAD 700 SIGMA EN/ES series valves are hydraulic, oblique pattern, globe valves with a raised seat assembly and double chamber unitized actuator, that can be disassembled from the body as a separate integral unit. The valves hydrodynamic body is designed for unobstructed flow path and provides excellent and highly effective modulation capacity for high differential pressure applications. The valves are available in the standard configuration or with an Independent Check Feature code "2S". The 700 SIGMA EN/ES Valves operate under difficult operation conditions with minimal cavitation and noise. They meet size and dimensions requirements of various standards.



[Click here for control accessories](#)



Features and Benefits

- Designed to - stand up to the toughest conditions
 - Excellent anti-cavitation properties
 - Wide flow range
 - High stability and accuracy
 - Drip tight sealing
- Double chamber design
 - Moderated valve reaction
 - Protected diaphragm
 - Optional operation in very low pressure
 - Moderated closing curve
- Flexible design - Easy addition of features
- Obstacle free flow pass

- V-Port Throttling Plug (Optional) - Very stable at low flow
- Compatible with various standards
- High quality materials
- In-line serviceable - Easy maintenance

Major Additional Features


- Solenoid control – 792-55-U
- Electric override – 792-59-U
- Downstream over-pressure guard – 792-48-U
- Electronic multi-level setting, Type 4T – 792-4T-U
- Independent Check Feature – 792-U-2S

See relevant BERMAD publication




Typical Installation

All images in this catalog are for illustration only



CLOSED

Regulating



This drawing refers to 1½ – 8"; 40-200 mm sized valves only. For other sizes please refer to the Model's IOM.

Main Valve

Valve Patterns: "Y" (Globe)

Size Range:

EN Series: 1½-16"; 40-400 mm

ES Series: 2½-24"; 65-600 mm

Pressure Rating: 25 bar; 400 psi

End Connections: Flanged (all standard)

Plug Types: Flat disc, V-port, Cavitation cage

Temperature Rating: 60°C; 140°F for Cold water applications

Optional higher temperature: Available on request

Standard Materials:

Body & actuator: Ductile Iron

Bolts, nuts & studs: Stainless Steel

Internals: Stainless Steel, Tin Bronze & Coated Steel

Diaphragm: Fabric-reinforced synthetic rubber

Seals: Synthetic rubber

Coating: Dark blue Fusion bonded epoxy

Control System

Standard Materials:

Accessories: Stainless Steel, Bronze & Brass

Tubing: Stainless Steel or Copper

Fittings: Stainless Steel or Brass

Pilot Standard Materials:

Body: Stainless Steel, Bronze or Brass

Elastomers: Synthetic Rubber

Spring: Stainless Steel

Internals: Stainless Steel

Pilot Options:

Various pilots and calibration springs are available.

Select according to valve size and operating conditions.

For more details check pressure reducing.

Orifice Assembly

Body: Fusion Bonded Epoxy Steel or Stainless Steel

Orifice Plate: Stainless Steel

Notes

- Burst flow settings should be at least 25% higher than the maximum allowed system flow
- Orifice diameter is calculated for each valve
- The orifice additional head loss is 0.2 bar ; 2.8 psi
- Orifice assembly adds 20-25mm ; ¾"-1" to valve length
- Recommended continuous flow velocity: 0.3-6.0 m/sec ; 1-20 ft/sec
- Minimum operating pressure: 0.7 bar ; 10 psi. For lower pressure requirements consult factory
- Inlet pressure, outlet pressure and flow rate are required for optimal sizing and cavitation analysis

