

Fire Protection Equipment Directory 2001

Underwriters Laboratories Inc



Guide Information <<http://database.ul.com>>

VLFT.EX6008

Special System Water Control Valves, Deluge Type

BERMAD CONTROL VALVES EX6008

4070 E LEAVERTON CT
ANAHEIM, CA 92807 USA

Deluge valves, Model 400E, rated pressure 175 psig, 2 in. size angle pattern for vertical installation and 2, 2-1/2, 3, 4, 6 and 8 in. size globe pattern for horizontal and vertical installation. For operation hydraulically, pneumatically, electrically, manually or combinations thereof. The height of the pilot line above the valve is limited as shown in the manufacturer's installation instructions. For use with Types 1 through 7 trim configurations as shown in the manufacturer's installation instructions.

Model 400E water control valve in the 2, 2-1/2, 3, 4, 6, 8 in. sizes may be supplied with optional pressure regulating trim additional feature "C" for Types 2 through 6 installed in accordance with the manufacturer's installation instructions.

Deluge valves, Model 700E, rated pressure 300 psig, 2, 2-1/2, 3, 4, 6, 8 and 10 in. size globe pattern for horizontal or vertical installation and 2, 3, 4, 6, 8 and 10 in. size angle pattern for vertical installation. For operation hydraulically, pneumatically, electrically, manually or combinations thereof. The height of the pilot line above the valve is limited as shown in the manufacturer's installation instructions. For use with Types 1 through 7 trim configurations as shown in the manufacturer's installation instructions.

Model 700E water control valve in the 2, 2-1/2, 3, 4, 6, 8 and 10 in. sizes may be supplied with optional pressure regulating trim additional feature "C" for Types 2 through 6 installed in accordance with the manufacturer's installation instructions.

Authorities having jurisdiction should be consulted before installation.

UL Listed and Classified Products