

Flow Control and Pressure Reducing Valve

with Hydraulic Control

IR-172-50-bD

The BERMAD Model IR-172-50-bD is a hydraulically operated, diaphragm actuated control valve that performs three independent functions. It limits system demand to a preset maximum flow rate; it reduces downstream pressure to maintain a constant preset maximum, and it either opens or shuts in response to a pressure command.



Features and Benefits

- Line Pressure Driven, Hydraulically Controlled On/Off
 - Limits fill-up rate and consumer over-demand
 - Protects downstream system
 - Easy flow and pressure setting
- Engineered Plastic Valve with Industrial Grade Design
 - Adaptable on-site to a wide range of end connection sizes and types
 - Articulated flange connections eliminate mechanical and hydraulic stresses
 - Highly durable, chemical and cavitation resistant
- hYflow 'Y' Valve Body with "Look Through" Design
 - Ultra-high flow capacity - Low pressure loss
- Unitized Flexible Super Travel (FST) Diaphragm and Guided Plug
 - Accurate and stable regulation with smooth closing
 - Requires low actuation pressure
 - Prevents diaphragm erosion and distortion
- Internal "Differential Pressure Duct" Flow Sensor
 - No moving parts
 - Saves space and simplifies installation



Typical Applications

- Computerized Irrigation Systems
- Line Fill-Up Control
- Multiple Independent Consumer Systems
- Pressure Reducing Stations
- Distribution Centers
- Filter Stations


[1] BERMAD Model IR-172-50-bD opens upon pressure drop command, limits fill-up rate and consumer over-demand, establishes reduced pressure zone, and maintains filter backwash pressure.

[2] BERMAD Relief Valve Model IR-13Q

[3] BERMAD Water Meter Model WPH

[4] BERMAD Air Valve Model ARA-A-P-P

BERMAD Irrigation



IR-I72-50-bD

For full technical details, refer to Engineering Section.

100 Series hYflow


Flow Control

Technical Specifications

Dimensions and Weights

Pattern	Size	DN Inch	Angle		Y (Oblique)			Y "Boxer"
			80-T ⁽¹⁾ 3-T ⁽¹⁾	80-T ⁽¹⁾ 3-T ⁽¹⁾	80-FC ⁽²⁾ 3-FC ⁽²⁾	80L-FC ⁽²⁾ 3L-FC ⁽²⁾	100-FC ⁽²⁾ 4-FC ⁽²⁾	150-FF ⁽³⁾ 6-FF ⁽³⁾
L (L1)	mm		187 (130)	298	308	310	350	480
	inch		7.4 (5.1)	11.7	12.1	12.2	13.8	18.9
H (Hf)	mm		235 (245)	180 (195)	240 (255)	280	294	285
	inch		9.3 (9.6)	7.1 (7.7)	9.4 (10)	11	11.6	11.2
C	mm		53	53	600	600	600	600
	inch		2.1	2.1	4	4	23.6	23.6
h	mm		117	50	100	100	112	145
	inch		4.6	2	3.9	3.9	4.4	5.7
Weight	Kg		1.6	1.6	4.4	5.9	7.6	12.5
	lb.		3.5	3.5	9.7	13	16.7	27.6

(1) "T" = Threaded end connections
 (2) "FC" = Flanged, Corona (Metal) end connections
 (3) "FF" = Flanged, Universal Plastic end connections



Technical Data

Sizes: 3, 3L, 4 & 6"; DN80, 80L, 100 & 150

Patterns:

Oblique: 3, 3L, 4 & 6"; DN80, 80L, 100 & 150

Angle: 3"; DN80

End Connections:

Threaded: 3 & 3"L; DN80 & 80L

Flanged: 3, 3L, 4 & 6"; DN80, 80L, 100 & 150

Pressure Rating: 10 bar; 145 psi

Operating Pressure Range: 0.35-10 bar; 5-145 psi

Setting Range: 1-7 bar; 15-100 psi

Setting ranges vary according to specific pilot spring. Please consult factory.

Flow Setting Range: ±20% from valve predetermined flow

The "Differential Pressure Duct" is pre-determined in accordance with the desired flow.

Materials:

Body, Cover and Plug: Glass-Filled Nylon

Diaphragm: NR, Nylon Fabric Reinforced


Seals: NR

Spring: Stainless Steel


Control Accessories: Plastic

Tubing and Fittings: Plastic

Flow Chart



Operation



Pressure Differential $[\Delta P]$ across the Differential Pressure Duct **[1]** is in direct proportion to demand. The Flow Pilot **[2]** continuously senses $[\Delta P]$ and commands the Valve to throttle closed should demand rise above pilot setting. The Pressure Reducing Pilot **[3]** controls the Valve to prevent Downstream Pressure **[P2]** from rising above pilot setting. The Hydraulic Relay Valve **[4]** closes upon pressure rise command, shutting the main Valve. The downstream Cock Valve **[5]** enables manual closing.

How to Order

Please specify the requested valve in the following sequence: (for more options, refer to Ordering Guide.)

Sector	Size	Primary Feature	Additional Feature	Pattern	Construction Materials	End Connections	Control Type	Voltage -Main Valve Position	Additional Attributes
IR	3-6"	172	50	Y	P	FF	2W/3W	-	bD
	Other sizes available on request.								
		Oblique Angle (3"; DN80 Only)	Y A		Threaded BSP (Female) Threaded NPT (Female) Plastic Flanges* Metal Flanges* ("Corona") Grooved (6"; DN150 Only)	BP NP FF CC VI	Servo Differential Pressure Duct Manual Selector Low Preset Pressure (below 2 bar) Plastic Pressure Test Point		b D Z 2 5

* Comply to: ISO PN10, ANSI #125/150, Jis K-10, BS-D

Other attributes available on request



info@bermad.com • www.bermad.com

The information herein is subject to change without notice. BERMAD shall not be held liable for any errors. All rights reserved. © Copyright by BERMAD. PC1AE72-50 05